

Both sided loading capacity mesh (Q)

| Mark | Diameter of the rod (mm) | | Space between rods (mm) | | Mesh Weight (kg) |
|-------|--------------------------|------|-------------------------|-----|------------------|
| | D | d | Pl | Pc | |
| Q62 | 4.0 | 4.0 | 200 | 200 | 13.39 |
| Q84 | 4.0 | 4.0 | 150 | 150 | 17.81 |
| Q92 | 4.2 | 4.2 | 150 | 150 | 19.63 |
| Q111 | 4.6 | 4.6 | 150 | 150 | 23.40 |
| Q126 | 4.0 | 4.0 | 100 | 100 | 26.39 |
| Q131 | 5.0 | 5.0 | 150 | 150 | 27.82 |
| Q138 | 4.2 | 4.2 | 100 | 100 | 29.12 |
| Q158 | 5.5 | 5.5 | 150 | 150 | 33.67 |
| Q166 | 4.6 | 4.6 | 100 | 100 | 34.58 |
| Q188 | 6.0 | 6.0 | 150 | 150 | 40.17 |
| Q196 | 5.0 | 5.0 | 100 | 100 | 41.21 |
| Q221 | 6.5 | 6.5 | 150 | 150 | 46.67 |
| Q238 | 5.5 | 5.5 | 100 | 100 | 49.92 |
| Q257 | 7.0 | 7.0 | 150 | 150 | 54.60 |
| Q283 | 6.0 | 6.0 | 100 | 100 | 59.15 |
| Q295 | 7.5 | 7.5 | 150 | 150 | 62.00 |
| Q331 | 6.5 | 6.5 | 100 | 100 | 69.55 |
| Q335 | 8.0 | 8.0 | 150 | 150 | 71.50 |
| Q378 | 8.5 | 8.5 | 150 | 150 | 79.82 |
| Q385 | 7.0 | 7.0 | 100 | 100 | 80.60 |
| Q402 | 8.0 | 8.0 | 125 | 125 | 83.07 |
| Q424 | 9.0 | 9.0 | 150 | 150 | 89.44 |
| Q442 | 7.5 | 7.5 | 100 | 100 | 92.56 |
| Q454 | 8.5 | 8.5 | 125 | 125 | 93.60 |
| Q472 | 9.5 | 9.5 | 150 | 150 | 100.10 |
| Q503 | 8.0 | 8.0 | 100 | 100 | 105.43 |
| Q524 | 10.0 | 10.0 | 150 | 150 | 110.50 |
| Q567 | 8.5 | 8.5 | 100 | 100 | 118.95 |
| Q577 | 10.5 | 10.5 | 150 | 150 | 118.17 |
| Q636 | 9.0 | 9.0 | 100 | 100 | 133.25 |
| Q692 | 10.5 | 10.5 | 125 | 125 | 141.18 |
| Q708 | 9.5 | 9.5 | 100 | 100 | 148.33 |
| Q785 | 10.0 | 10.0 | 100 | 100 | 164.71 |
| Q753 | 12.0 | 12.0 | 150 | 150 | 156.29 |
| Q1130 | 12.0 | 12.0 | 100 | 100 | 226.44 |